





Contrad® 100 is a low-foaming alkaline liquid detergent formulated for Clean-In-Place systems.

Contrad® 100 is effective in removing a wide variety of contaminants from stainless steel, glass, and plastic surfaces. Its low-foaming characteristics prevent

pump cavitation and excessive residual foam.

Contrad® 100 is extremely free-rinsing, phosphate-free and disposable straight to the drain.

| Packaging | | |
|-------------------|----------|---------|
| Size | Case QTY | Decon # |
| 1 Gallon (3.8L) | 4 | 1504 |
| 5.28 Gallon (20L) | - | 1503 |
| 30 Gallon (115L) | - | 1506 |
| 55 Gallon (210L) | - | 1505 |

PRECAUTIONARY STATEMENT: Contrad® 100 is alkaline and therefore is a severe eye irritant and mild skin irritant. Always wear eye protection gloves, and appropriate protective clothing when handling. Because of high pH value, Contrad® 100 should never be used to clean non-ferrous metals.

DIRECTIONS FOR USE: Contrad® 100 is supplied as a concentrate for dilution. Deionized water is preferred for preparing working solutions. CIP systems and other pressure washing equipment will be equipped with an automatic pumping system which dispenses the concentrate into the flow of water at a specified rate. If this is the case, simply place the machines dip tube into the container of Contrad 100 and adjust the pump to meter out the appropriate amount.

The required concentration of **Contrad® 100** will vary accordingly to the severity of cleaning task. Solution strengths between 0.5 % and 5 % v/v are the most commonly employed. The solution strength and temperature can be increased to handle extremely stubborn or water-resistant contamination.

RINSABILITY: Contrad® 100 is extremely free-rinsing, so it is ideal for critical cleaning applications in pharmaceutical, biotechnology, and medical device process equipment. Rinsing with copious amounts of deionized water is sufficient to remove all residual cleaning solution.

GMP VALIDATION & RESIDUE DETECTION: Contrad® 100 may be used in process equipment that require GMP validation, In these applications, it will be necessary to detect and qualify the amounts of trace residues in order to determine if these residues fall within the allowable limits. Analytical methods used to detect and quantify trace residues include Total Organic Carbon (TOC), HPLC, UV-VIS, Conductivity, Ion Chromatography, Titration, Calorimetry and others.

DISPOSAL: Contrad® 100 contains no generally recognized pollutants and therefore may be disposed straight to drain with adequate dilution and/or neutralization.

Rev. 07/2021